

## LAMIERA NERA A CALDO DERIVATA DA COILS

S235JR (EN 10025 +A1)

Spessore mm	FORMATI mm			
	1000x 2000	1250x 2500	1500x 3000	2000x 6000
1,5	24	37,5	54	-
2,0	32	50	72	-
2,5	40	62,5	90	-
3,0	48	75	108	288
4,0	64	100	144	384
5,0	80	125	180	480
6,0	96	150	216	576
7,0	112	175	252	672
8,0	128	200	288	768
10,0	160	250	360	960
12,0	192	300	432	1152
15,0	240	375	540	1440
20,0	314	490	706	-

## LAMIERE Fe

Spessore mm	LAMIERA DECAPATA DD11 (EN 10111)				LAMIERA A FREDDO DC01 (EN 10130 + A1)			LAMIERA ZINCATA DX51 D (UNI EN 10327: 2004)		
	FORMATI mm									
	1000x 2000	1250x 2500	1500x 3000	2000x 4000	1000x 2000	1250x 2500	1500x 3000	1000x 2000	1250x 2500	1500x 3000
0,3	-	-	-	-	-	-	-	4,8	-	-
0,4	-	-	-	-	-	-	-	6,4	-	-
0,5	-	-	-	-	8	12,5	18	8	12,5	-
0,6	-	-	-	-	9,6	15,0	21,6	9,6	15	21,6
0,8	-	-	-	-	12,8	20,0	29	12,8	20	28,8
1,0	-	-	-	-	16	25,0	36	16	25	36
1,2	-	-	-	-	19,2	30,0	43	19,2	30	43,2
1,5	24	37,5	53	-	24	37,5	53	24	37,5	53
2,0	32	50	72	96	32	50,0	72	32	50	72
2,5	40	62,5	90	128	40	62,5	90	40	62,5	90
3,0	48	75	108	192	48	75,0	108	48	75	108
4,0	64	100	144	256	-	-	-	64	100	144
5,0	80	125	180	320	-	-	-	-	-	-
6,0	96	150	216	-	-	-	-	-	-	-
7,0	112	175	252	-	-	-	-	-	-	-
8,0	128	200	288	-	-	-	-	-	-	-
10,0	160	250	360	-	-	-	-	-	-	-
12,0	192	300	432	-	-	-	-	-	-	-
15,0	240	375	530	-	-	-	-	-	-	-

= materiale disponibile a magazzino