



TUBI SALDATI TONDI "CARPENTERIA" (EN 10219 -1 - 2)

Dimensioni		Spessore S in millimetri						
Diametro		1,2	1,5	2	3	4	5	6
mm	pollici	Peso kg/m						
12		0,32	0,39					
14		0,38	0,49					
16		0,44	0,54	0,69				
16,75	3/8			0,73				
18		0,5						
20		0,55	0,68					
21,25	1/2		0,73	* 0,96				
22		0,62						
25				1,13				
26,75	3/4		0,93	1,22	* 1,76			
28		0,79			1,85			
30		0,86		1,39				
32		0,91			2,14			
33,48	1				* 2,25		3,45	
35		1,00			2,37			
38		1,10			2,59			
40		1,15		1,87	2,74			
42,25	1 1/4	1,23		2,01	* 2,90	3,79		
45		1,30		2,12	3,11			
48,25	1 1/2	1,41		2,30	* 3,35	4,37	5,30	
50		1,45	* 1,80	2,38	3,48			
51			1,87	2,47	3,63			
54			1,94		3,77			
55			1,98	2,61	3,85			
57		1,67	2,05	2,74				
60,3	2	1,76		2,90	* 4,22	5,55	6,78	
63,5			2,29	3,04	4,48	5,86		
65			2,35	3,11	4,59			
70			2,53	3,37	4,96			
76,1	2 1/2			3,68	* 5,40	7,11	8,75	10,36
80				3,85	5,70	7,50		
83				3,99	5,92	7,79	9,61	
88,9	3			4,32	6,36		10,35	12,28
95				4,59	6,81	8,98		
101,6	3 1/2			4,91	7,29	9,63	11,91	
108				5,27		10,46	12,90	15,54
114,3	4			5,58	8,25	10,88	13,48	16,03
121				5,87	8,73		14,31	
127	4 1/2			6,15	9,17		15,04	
133							15,80	18,78
139,7	5				10,13		16,60	
152,4	5 1/2				11,06			
159					11,57	15,40	19,00	
168,3	6				12,22	16,22	20,15	24,02
193,7	7				14,12	18,72	21,92	27,77
219,1	8				16,00	21,23	26,40	31,53
273	10					26,70	33,00	38,86
323,9	12					31,56	39,32	46,27
355,6	14					34,68		50,88

 = materiale disponibile a magazzino

* = materiale disponibile anche zincato