








GRIGLIATI ELETTROFORGIATI: TIPI DI PRODUZIONE

Maglia	Piatto		2		3		2		3		2		3		4		4	
	Dimensioni grate	20	25	25	25	30	30	30	30	30	30	40	40	40	50	60	70	
	15 x 76	Ø 22,6	Ø 27,9	Ø 27,9	Ø 33,2	Ø 48,9	Ø	Ø	Ø	Ø	Ø	Ø	Ø	Ø	Ø	Ø	Ø	Ø
	25 x 76	14,5	Ø 17,7	Ø 17,7	Ø 20,9	Ø 30,6	Ø 27,4	Ø	Ø	Ø	Ø	Ø	Ø	Ø	Ø	Ø	Ø	Ø
	34 x 76		Ø 13,5	Ø 13,5	Ø 15,9	Ø 23,0	Ø 20,6	Ø	Ø	Ø	Ø	Ø	Ø	Ø	Ø	Ø	Ø	Ø
	64 x 132		Ø 7	Ø 7		13,4												
	22 x 38		Ø 21,5	Ø 21,5		36,0												
	34 x 38		Ø 15,1	Ø 15,1	Ø 17,5	Ø 24,6	Ø 22,2	Ø	Ø	Ø	Ø	Ø	Ø	Ø	Ø	Ø	Ø	Ø
	60 x 66		Ø 9,2	Ø 9,2		14,6												

Ø = materiale disponibile a mezzazino

* = materiale disponibile anche zincato





TABELLE DEI CARICHI GRIGLIATI



		DISTANZA NETTA FRA GLI APOGGI IN MM.												
Maglie	Piatti	300	400	500	600	700	800	900	1000	1200	1400	1600	1800	2000
34x 38	25x 2	9000	5000	3200	2200	1630	1200	830	600	350	220	150	100	
		710	450	330	260	215	185	150	120					
34x 76	30x 2	12800	7200	4600	3200	2350	1800	1420	1050	600	380	260	180	130
		1030	650	480	380	310	265	230	205	145	100			
34x 38	25x 3	13400	7500	4800	3400	2500	1800	1250	910	530	330	220	160	110
		1070	680	500	400	330	280	220	180	125				
34x 76	30x 3	19200	10800	6900	4800	3500	2700	2150	1570	910	570	380	270	200
		1540	980	720	570	470	400	350	310	215	155	120		
34x 38	40x 3	34100	19200	12300	8500	6300	4800	3800	3100	2130	1360	910	640	470
		2740	1740	1280	1010	830	710	620	550	445	380	280	220	180
34x 76	40x 4	45500	25600	16400	11400	8400	6400	5100	4100	2850	1810	1210	850	620
		3650	2320	1700	1350	1110	950	830	730	600	500	380	300	240
34x 38	50x 4	71000	40000	25600	17800	13100	10000	7900	6400	4500	3300	2500	2000	1200
		5700	3630	2660	2100	1740	1480	1290	1140	930	780	680	600	470
34x 76	60x 4	102000	58000	37000	25600	18800	14400	11400	9200	6400	4700	3600	2850	2100
		8210	5230	3830	3030	2500	2130	1860	1640	1340	1130	980	860	770
34x 38	70x 4	140000	78400	50200	34800	25600	19600	15500	12500	8700	6400	4900	3900	3200
		11200	7110	5210	4110	3400	2900	2520	2240	1820	1540	1330	1170	1040

1 da N = 1 Kg.

I carichi riportati in tabella sono stati calcolati considerando un carico di sicurezza K = 1600 da N./cmq. ed una freccia elastica minore o uguale a 1/200 della luce libera di appoggio